

H216

Key Specs

Weight Without Rotator and Link - 1490 kg

Maximum Cut Diameter - Standard: 750
Top Saw: 400 mm

Maximum Roller Opening - 700 mm

Dimensions

Width, Head Open - 1695 mm

Width, Head Closed - 1335 mm

Height Without Rotator and Link - 1845 mm

Weight Without Rotator and Link - 1490 kg

Felling/Cutting

SuperCut 100S Saw Unit, Automatic Chain Tensioning - Standard, Top Saw

Maximum Cut Diameter - Standard: 750
Top Saw: 400 mm

Length Of Saw Bar - Standard: 900; Top Saw: 600 mm

Chain Type - 404

Chain Speed - 40 m/s

Feed System, Two-Wheel-Drive

Maximum Feed Speed - 4,2-6,3 m/s

Maximum Roller Opening - 700 mm

Delimbing

Delimbing Knives - 4 moving and 1 fixed
Delimbing Diameter, Tip To Tip - 450 mm
Maximum Opening Upper Knives - 700 mm
Maximum Opening Lower Knives - 760 mm

Hydraulic System

Maximum Operating Pressure - 28/35 (option) MPa
Recommended Pump Capacity - 260-370 L/min

Tank Capacities

Color Marking - Yes
Color Marking - 1.4 L
Chain Oil - 14.0 L
Chain Grease - 1.2 kg

Optional Equipment

Stump Treatment - Yes
Multi-Tree-Handling (MTH) - Yes
Mense Feed Rollers - Yes
Steel Thumbnail Feed Rollers - Yes
Steel Ribbed Feed Rollers - Yes
Chain And Saw Bar Kits - Yes
Hydraulic Hose Kit - Yes
Top Saw - Yes